

# Metreau® 7-Button Ethernet Expansion Keypad

MET-7X-WH (FG5793-13-WH), White

MET-7X-BL (FG5793-13-BL), Black



## Overview

The MET-7X Metreau 7-Button Expansion Keypad connects to any adjacent Metreau Ethernet Keypad (MET-6NE, MET-7E or MET-13E) via ribbon-cable to add additional control points in the same location.

## Common Applications

The MET-7X is Ideal for classrooms, conference rooms, residences or hotels that require multiple adjacent control points.

## Features

- **Simple Connection** – Connect up to three keypads with one IP address to optimize the room’s network design
- **Power Over Ethernet (PoE) Compatible** – The Expansion Keypad receives power from the Metreau Ethernet Keypad it is connected to (options include MET-6NE, MET-7E and MET-13E) via the ribbon cable

**NOTE: Keypad wallplates not included. See ALD-CW-1, ALD-CW-2, ALD-CW-3**

## Specifications

GENERAL	
Dimensions (HWD)	Keypad and Mounting Plate: 4" x 1 3/4" x 1" (10.3 cm x 4.5 cm x 2.5 cm)
Weight	TBA
Mounting	Mounts into standard Decora-style wall plates
Colors Available	White: MET-7X-WH (FG5793-13-WH)

	Black: MET-7X-BL (FG5793-13-BL)
Included Accessories	16-conductor ribbon-cable
Recommended Accessories	<ul style="list-style-type: none"> <li>•ALD-CW-1, 1-Gang Claro Wallplate (FG2605-81-BL / FG2605-81-WH)</li> <li>•ALD-CW-2, 2-Gang Claro Wallplate (FG2605-82-BL / FG2605-82-WH)</li> <li>•ALD-CW-3, 3-Gang Claro Wallplate (FG2605-83-BL / FG2605-83-WH)</li> </ul>

<b>POWER</b>	
PoE	The Expansion Keypad receives power from the Metreau Ethernet Keypad it is connected to (options include MET-6NE, MET-7E and MET-13E) via the ribbon cable, see the Ethernet Keypad data sheet for PoE specifications

<b>ENVIRONMENTAL</b>	
Temperature (Operating)	32° to 104° F (0° to 40° C)
Humidity (Relative)	5% to 85%, non-condensing
Note	Intended for indoor use only

<b>FRONT PANEL COMPONENTS</b>	
Front Panel Components	<ul style="list-style-type: none"> <li>•Pushbuttons available in a variety of field replaceable pre-printed buttons</li> <li>• Blue LEDs indicate activity</li> </ul>

<b>REAR PANEL COMPONENTS</b>	
Rear Panel Components	(2) 8-pin, 0.100" (2.54 mm) IDC-type male header

**About AMX**

AMX hardware and software solutions simplify the implementation, maintenance, and use of technology to create effective environments. With the increasing number of technologies and operating platforms at work and home, AMX solves the complexity of managing this technology with reliable, consistent and scalable systems. Our award-winning products span control and automation, system-wide switching and audio/video signal distribution, digital signage and technology management. They are implemented worldwide in conference rooms, homes, classrooms, network operation / command centers, hotels, entertainment venues, broadcast facilities, and more. ©2013 AMX. All rights reserved.

Specifications subject to change. Revised 17-June-14.

AMX.com | 800.222.0193 | 469.624.8000 | +1.469.624.7400 | fax 469.624.7153