

JPEG 2000 Digital Cinema Grade Video over IP Decoder

NMX-DEC-N2211 (FGN2211-SA), Stand Alone

NMX-DEC-N2211-C (FGN2211-CD), Card



Overview

The AMX SVSI N2000 Series utilizes JPEG2000 compression for HD, cinema-grade video distribution on the LAN for applications when video quality is top priority. The NMX-DEC-N2211 Decoder is used to decode streams back to DVI or HDMI format for display on any monitor. Pair with the NMX-ENC-N2121 to encode and distribute sources of almost any format onto an existing IP network making that stream available to any endpoint in the facility. With the ability to direct any source stream to any display, large, low-cost switching and distribution systems are simple to deploy without proprietary cabling or dedicated switching hardware.

The NMX-DEC-N2211 includes Local Play, allowing users to upload and save 8 playlists that can contain up to 64 jpeg or PNG files. When a video stream is lost, the stored images will play, preventing blank displays.

Includes serial and single network port. Digital video output only.

Common Applications

- The NMX-DEC-N2211 is the perfect solution for matrix switching and distribution of HD, cinema-grade quality video over LAN. Common applications include enterprise, house of worship, entertainment, and stadiums.

Features

- **Input and Output Scaling** – Video scaling at either input or output allows seamless switching from any source, at any resolution, to any display or projector, while preserving video fidelity.
- **Plug-n-Play** –Auto-detect technology reduces installation and programming time.
- **Onboard Control** – All N-Series encoders and decoders have on-board, built-in control capability via events that can trigger any number of TCP/UDP commands to other IP controllable devices.
- **Unlimited Scalability**

- **Stand Alone or Card** – Available as a stand alone device, or card for use with NMX-ACC-N9206.

Specifications

| VIDEO | |
|---------------------|---|
| Digital Video Input | Network video over Ethernet via RJ45 port |
| Video Output | DVI-D, HDMI HDMI is supported through a passive adapter |
| Formats | DVI-D, HDMI (through adapter), Dual-Mode DisplayPort (DP++), HDCP content protection support, RGBHV, YPbPr HDMI and Dual-Mode DisplayPort (DP++) are supported through a passive adapter |
| Output Resolutions | Supports most common HD resolutions up to 1080p60. See website for all supported resolutions. |

| AUDIO | |
|---------------------|---|
| Input Signal Types | Network video over Ethernet via RJ45 |
| Output Signal Types | Embedded audio on DVI-D or HDMI (through adapter) |
| HDMI Audio Formats | 8ch PCM |

| LATENCY | |
|---------|--|
| Latency | 170 ms |
| Note: | <i>Scaling can add up to 16 ms of latency.</i> To calculate an end-to-end latency value, add the given Decoder latency (shown above) to your Encoder's latency (which is provided in the Encoder's Specifications sheet). |

| COMMUNICATIONS | |
|----------------|---|
| Ethernet | 10/100/1000 Mbps, auto-negotiating, auto-sensing, full/half duplex, DHCP, Auto IP, and Static IP. |
| HDMI | HDCP, EDID management |

| PORTS | |
|-----------|---|
| +12V 2A | One 12 Volt DC power input |
| P1 | 8-wire RJ45 female 10/100/1000 Mbps 10/100/1000Base-T auto-sensing gigabit Ethernet switch port. Provides network connection |
| RS232 | 3-pin terminal Phoenix connector which provides a serial control interface. Full duplex communication. Available terminal speed settings: 1200-115200 baud rate |
| DVI-D OUT | DVI-D female; HDMI/DVI digital video/audio output. Allows for video and embedded digital audio output. |

| CONTROLS AND INDICATORS – FRONT PANEL | |
|---------------------------------------|---|
| RESET Button | Recessed pushbutton Press to initiate a 'warm restart' causing the processor to reset, but not lose power. A reset does NOT affect the |

| | |
|------------|---|
| | current settings |
| ID Button | Recessed pushbutton Press to send a notification out on the network to identify the unit (the notification causes a pop-up dialog in N-Able and N-Command) |
| POWER LED | On solid (green) when operating power is supplied (via PoE or local power supply) This activity is also shown by the PWR LED on the rear panel |
| STATUS LED | On flashing (green) when there is software activity This activity is also shown by the STAT LED on the rear panel |

| CONTROLS AND INDICATORS – REAR PANEL | |
|--------------------------------------|---|
| PWR LED | Same as POWER LED described above |
| HDMI LED | On (green) when there is a connection to a valid video source |
| STAT LED | Same as STATUS LED described above |
| STRM LED | On (green) when the unit is streaming video |

| POWER SUPPLY | |
|----------------------------------|--|
| Power Supply, External, Included | 2.0 Amp @ 12 Volts DC; 100-240 Volts AC power supply; Included in shipment. NMX-ACC-N9312 (FGN9312) |

| ENVIRONMENTAL | |
|------------------|--------------------------------|
| Temperature | 32° to 104°F (0° to 40°C) |
| Humidity | 10% to 90% RH (non-condensing) |
| Heat Dissipation | Up to ~44 BTU/hr |

| GENERAL | |
|-------------------------|---|
| Dimensions (HWD) | 1.05" x 7.888" x 5" (2.67 cm x 20.04 cm x 12.7 cm) |
| Weight | 1.4 lbs (0.64 kg) |
| Mounting Options | Stand alone, surface mount, wall mount, or rack mount Surface and wall mounting requires (not included): <ul style="list-style-type: none"> •NMX-ACC-N9101 (FGN9101), Mounting Wings for SVSI N-Series Encoders and Decoders Rack mounting requires one of the following (not included): <ul style="list-style-type: none"> •NMX-ACC-N9102 (FGN9102), 1RU Rack Shelf for Two Side-by-Side for SVSI N-Series Encoders and Decoders •NMX-ACC-N9206 (FGN9206), 2RU Rack Mount Cage with Power for Six SVSI N-Series Card Units |
| Regulatory Compliance | FCC, CE, and NTRL |
| Recommended Accessories | <ul style="list-style-type: none"> •NMX-ACC-N9382 (FGN9382), 1RU Power Supply 16-Channel 12V for up to 16 SVSI N-Series Encoders and Decoders •NMX-ACC-N9101 (FGN9101), Mounting Wings for SVSI N-Series Encoders and Decoders •NMX-ACC-N9102 (FGN9102), 1RU Rack Shelf for Two Side-by-Side SVSI N-Series Encoders and Decoders |

•NMX-ACC-N9206 (FGN9206), 2RU Rack Mount Cage with Power for Six SVSI N-Series Card Units


NMX-DEC-N2211 Front View



- 1) Device reset button
- 2) Device ID discovery button

- 3) Power/Status indicators

NMX-DEC-N2211 Rear View



- 1) 12VDC Input
- 2) Status Indicators
- 3) RJ-45 auto-sensing gigabit ethernet switch port

- 4) RS232 connection
- 5) DVI-D Digital Output

About AMX by HARMAN

Founded in 1982 and acquired by HARMAN in 2014, AMX® is dedicated to providing AV solutions for an IT World. AMX solves the complexity of managing technology with reliable, consistent and scalable systems comprising control, video switching and distribution, digital signage and technology management. AMX systems are deployed worldwide in conference rooms, classrooms, network operation/command centers, homes, hotels, entertainment venues and broadcast facilities, among others. AMX is part of the HARMAN Professional Group, the only total audio, video, lighting, and control vendor in the professional AV market. HARMAN designs, manufactures and markets premier audio, video, infotainment and integrated control solutions for the automotive, consumer and professional markets. Revised 12.7.15. ©2015 Harman. All rights reserved. Specifications subject to change.

www.amx.com | +1.469.624.7400 | 800.222.0193