

Power Supply Models

AMX offers 6 variations of our Class I, CSA/CE approved, and UL listed system power supplies:

| PS/N/R POWER SUPPLIES | | |
|-----------------------|-------------------|--|
| PSN6.5 | (FG423-41) | With US power cord |
| PS4.4 | (FG423-44) | Includes US power cord and barrel plug |
| PS3.0 | (FG423-30) | Includes US power cord and barrel plug |
| PSR2.5 | (FG423-47) | Includes 3-pin retained captive-wire connector and US power cord |
| PSR5.4 | (FG423-48) | Includes 2-pin retained captive-wire connector and US power cord |
| PSR7-V | (FG423-49) | IEC power cord provided as a separate part, dependent on country requirements. |

Note: All models use an input connector sanctioned by the IEC (International Electrotechnical Commission).

PSN6.5 Specifications

FIG. 1 displays the rear panel of the PSN6.5.



FIG. 1 PSN6.5 POWER SUPPLY

| PSN6.5 SPECIFICATIONS | |
|------------------------|---|
| Dimensions (HWD): | 1 1/2" x 5 9/16" x 9 1/4" (3.81 cm x 14.10 cm x 23.50 cm) |
| Weight: | 2.76 lbs. (1.25 kg) (without power cord) |
| Input: | ~100-240 V, 2.6A MAX (1.3A MAX @ 230), 50/60 Hz |
| Output Voltage: | 13.5 V $\overline{\text{---}}$ |
| Output Current: | 6.5 A (continuous power output is 90 W max) |
| Ripple and Noise: | 350 mV peak-to-peak @ 70% load |
| Protection: | Over-voltage, over-current, short-circuit, transient and thermal switching regulated, overload protected |
| Power Indicator: | Green LED indicates presence of DC on the output. |
| Connectors: | Three removable 2-pin 3.5 mm mini-Phoenix connectors |
| Rear Panel Components: | <ul style="list-style-type: none"> • Three 12 V $\overline{\text{---}}$ power supply connectors • Standard IEC (male) jack for the power cord |
| Input Power Cord: | 6-foot (1.83 m) IEC cord with a grounded Edison plug for AC input (US only) |
| Enclosure: | Metal with black matte finish |
| Temp Range: | 32°F - 122°F (0°C - 50°C) |
| Certification: | <ul style="list-style-type: none"> • UL: US listed - Class I Power Supply • CSA approved • CE approved • PSE approved • CCC approved |
| Accessories: | <ul style="list-style-type: none"> • US power cord • 3 removable 2-pin 3.5 mm mini-Phoenix connectors • (Optional) AC-RK Accessory Rack Kit (FG515) |

PS4.4 Specifications

FIG. 2 displays the PS4.4.



FIG. 2 PS4.4 POWER SUPPLY

| PS4.4 SPECIFICATIONS | |
|-----------------------|---|
| Dimensions: | 4 5/8" x 2 1/4" x 1 1/2" (11.7 cm x 5.8 cm x 3.5 cm) |
| Weight: | 1.1 lb. (499 g) |
| Input: | ~100-240 V, 1.5A MAX (0.6A MAX @ 230), 50/60 Hz |
| Output Voltage: | 13.5 V $\overline{\text{---}}$ |
| Output Current: | 4.5A MAX |
| Ripple and Noise: | 150 mV peak-to-peak @ full load |
| Protection: | Over-voltage, over-current, short-circuit, transient and thermal. Switching regulated, overload protected. |
| Power Indicator: | Green LED indicates the presence of V $\overline{\text{---}}$ on the output. |
| Connector: | Barrel plug (2.1mm ID, 5.5mm OD, 9.5mm length) |
| Input Power Cord: | 6-foot (1.83 m) IEC cord with a grounded Edison plug for AC input (US only) |
| Enclosure: | Molded black matte plastic |
| Temp Range: | 32°F - 104°F (0°C - 40°C) |
| Certification: | <ul style="list-style-type: none"> • UL: US listed - Class I Power Supply • CSA approved • CE approved • PSE approved |
| Included Accessories: | US power cord |

PS3.0 Specifications

FIG. 3 displays the PS3.0. The PS3.0 is a Class I power supply which is CE approved and UL listed. The PS3.0 uses a barrel-plug connector.



FIG. 3 PS3.0 POWER SUPPLY

| PS3.0 SPECIFICATIONS | |
|-----------------------|---|
| Dimensions (HWD): | 3 7/8" x 1 3/4" x 1 1/4" (9.8 cm x 4.5 cm x 3.05 cm) |
| Weight: | 5.6 oz (150 g) (without power cord) |
| Input: | ~100-240 V, 3A MAX, 50/60 Hz |
| Output Voltage: | 13.5 V $\overline{\text{---}}$ |
| Output Current: | 2.66 A |
| Ripple and Noise: | 200 mV (60Hz Ripple + Switching ripple and noise) |
| Protection: | Over-voltage, over-current, short-circuit, transient and thermal switching regulated, overload protected |
| Power Indicator: | Green LED indicates presence of DC on the output. |
| Connectors: | 1.3mm barrel plug, 11 mm long |
| Input Power Cord: | 6-foot (1.83 m) IEC power cord terminated with a grounded Edison plug for AC input (US only). |
| Enclosure: | Molded black matte plastic |
| Temp Range: | <ul style="list-style-type: none"> • Operating temperature: 32°F - 122°F (0°C - 50°C) • Storage temperature: -4°F - 185°F (-20°C - 85°C) |
| Certification: | <ul style="list-style-type: none"> • UL: US listed - Class I Power Supply • CUL approved • TUV approved • FCC approved • CE approved • PSE approved |
| Included Accessories: | US power cord |

PSR2.5 Specifications

FIG. 4 displays the PSR2.5.



FIG. 4 PSR2.5 POWER SUPPLY

| PSR2.5 SPECIFICATIONS | |
|-----------------------|---|
| Dimensions (HWD): | 4 3/4" x 2 3/8" x 1 1/4" (12 cm x 6 cm x 3.05 cm) |
| Weight: | 1.1 lb. (499 g) |
| Input: | ~100-240 V, 1.5A MAX, 47/63 Hz |
| Output Voltage: | 24 V $\overline{\text{---}}$ |
| Output Current: | 2.5 A |
| Ripple and Noise: | 300 mV peak-to-peak @ full load |
| Protection: | Over-voltage, over-current, short-circuit, over temperature, overload protected |
| Power Indicator: | Green LED indicates presence of DC on the output. |
| Connectors: | 3-pin retained captive wire connector (3.5mm) |
| Input Power Cord: | 4-foot (1.2 m) IEC power cord terminated with a grounded Edison plug for AC input (US only). |
| Enclosure: | Molded black matte plastic |
| Temp Range: | <ul style="list-style-type: none"> Operating temperature: 32°F - 104°F (0°C - 40°C) Storage temperature: -4°F - 176°F (-20°C - 80°C) |
| Certifications: | <ul style="list-style-type: none"> UL: US listed - Class I Power Supply CUL approved TUV-GS approved FCC approved CE approved PSE approved CCC approved BSMI approved RCM approved |
| Included Accessories: | US power cord |

PSR5.4 Specifications

FIG. 5 displays the PSR5.4.



FIG. 5 PSR5.4 POWER SUPPLY

| PSR5.4 SPECIFICATIONS | |
|-----------------------|--|
| Dimensions (HWD): | 4 1/2" x 2" x 1 1/4" (11.5 cm x 5.15 cm x 3.05 cm) |
| Weight: | 0.48 lb (221 g) |
| Input: | 100-240 +10% VAC, 47-63 Hz |
| Input Current: | <ul style="list-style-type: none"> <2A MAX at 100 VAC + full load <1A MAX at 230 VAC + full load |
| Output Voltage: | 12 V $\overline{\text{---}}$ |
| Output Current: | 5.4A MAX |
| Ripple and Noise: | 200 mV peak-to-peak @ full load |

PSR5.4 SPECIFICATIONS (CONT.)

| | |
|-----------------------|---|
| Protection: | Over-voltage, over-current, short-circuit, transient and thermal. Switching regulated, overload protected |
| Power Indicator: | Green LED indicates the presence of DC on the output |
| Connectors: | Mini 2-pin captive wire connector (3.5 mm) |
| Input Power Cord: | 50 mm IEC power cord terminated with a grounded Edison plug for AC input |
| Enclosure: | Molded black matte plastic |
| Environmental: | <ul style="list-style-type: none"> Operating temperature: 32°F to 104°F (0°C to 40°C) Storage temperature: -4°F - 176°F (-20°C - 80°C) |
| Certifications: | <ul style="list-style-type: none"> UL: US listed - Class I Power Supply, CSA approved, CE approved AS/NZS 60950-1 - Australia, New Zealand BSMI - Taiwan CCC - China CU - Russia UL Energy Verified KC - Korea TUV GS - Germany |
| Included Accessories: | US power cord |

PSR7-V Specifications

FIG. 6 displays the PSR7-V. This accessory power supply should be used only with Listed AMX products.



FIG. 6 PSR7-V POWER SUPPLY

| PSR7-V SPECIFICATIONS | |
|--------------------------|--|
| Dimensions (HWD): | 1 5/8" x 5 3/4" x 5 1/8" (4.13 cm x 14.6 cm x 13.02 cm) |
| Weight: | 1.45 lb. (657 g) |
| Input: | ~100-240 V, 1.9A MAX, 47/63 Hz |
| Output Voltage: | 12 V $\overline{\text{---}}$ +/- .6V |
| Output Current: | 5.5 A |
| Ripple and Noise: | 160mV peak-to-peak @ full load |
| Protection: | Over-voltage, over-current, short-circuit, over temperature, overload protected |
| Power Indicator: | Green LED indicates the presence of DC on the output |
| Connectors: | Three removable 2-pin 3.5 mm mini-Phoenix connectors |
| Input Power Cord: | Dependent on regional model number. Please see the product catalog for available country-specific products. |
| Output Power Connectors: | <ul style="list-style-type: none"> Three 12 V $\overline{\text{---}}$ power supply connectors The connecting cable must be DP-2 or DP-2P and proper AWG. |
| Enclosure: | Metal with black matte finish |
| Environmental: | <ul style="list-style-type: none"> Operating temperature: 32°F to 122°F (0°C to 50°C) Storage temperature: -4°F - 176°F (-20°C - 80°C) <p>Note: If mounting the power supply on a rack, you must keep 1 RU clear between items to ensure a proper temperature environment.</p> |
| Certifications: | <ul style="list-style-type: none"> UL/cUL/CB UL AR UL, RCM -Australia, New Zealand UL - Morocco NOM - Mexico FCC Part 15 Subpart B CCC - China |

Note: The power light on the front panel should remain solid when power is provided to the unit. A blinking power light indicates overcurrent. If this occurs, unplug the main power connector from the unit for 30 seconds then reconnect the power to reset the unit. If the main power is connected and the power light is not on, the unit has overheated. If this occurs, unplug the main power connector from the unit for 30 seconds then reconnect the power to the unit.



© 2017 Harman. All rights reserved. AMX, AV FOR AN IT WORLD, HARMAN, and their respective logos are registered trademarks of HARMAN. AMX does not assume responsibility for errors or omissions. AMX also reserves the right to alter specifications without prior notice at any time. The AMX Warranty and Return Policy and related documents can be viewed/downloaded at www.amx.com.
 3000 RESEARCH DRIVE, RICHARDSON, TX 75082 AMX.com | 800.222.0193 | 469.624.8000 | +1.469.624.7400 | fax 469.624.7153
 AMX (UK) LTD, AMX by HARMAN - Unit C, Auster Road, Clifton Moor, York, YO30 4GD United Kingdom ? +44 1904-343-100 ? www.amx.com/eu/

93-0423-41 REV: S



Last Revised: 2024-09-11