

Metreau® 6-Button Ethernet Keypad with Navigation

MET-6NE-WH (FG5793-01-WH), White

MET-6NE-BL (FG5793-01-BL), Black



Overview

The MET-6NE Metreau 6-Button Ethernet Keypad with Navigation features source control, a navigation wheel that adjusts levels and provides up, down, left, right and select button options, as well as an LED bar for visual level feedback. The MET-6NE can be used as an individual keypad or in conjunction with the 7 or 13-Button Metreau Ethernet Expansion Keypads. The Keypad connects to the controller via Ethernet, which simplifies installation and connectivity.

Common Applications

Ideal for cost effective control for classrooms, conference rooms, kitchens, bathrooms, and other applications requiring simplified control up to 6 devices.

Features

- **Connects via Standard Protocols (Ethernet)** – Simplifies cabling and installation by minimizing cable runs
- **Daisy Chain up to Three Keypads** – Provides the ability to connect up to three keypads using one IP address
- **Fits in Decor Style Wall Plates** – Simplifies installation and looks great
- **Blue LEDs Glow to Indicate Button Selection** – Improves usability by confirming the user's choice
- **Unrivaled Simplicity** – navigation navigation wheel for simplified control

NOTE: Keypad wallplates not included. See ALD-CW-1, ALD-CW-2, ALD-CW-3.

Specifications

GENERAL	
Dimensions (HWD)	Keypad and Mounting Plate: 4" x 1 3/4" x 1" (10.3 cm x 4.5 cm x 2.5 cm)
Weight	TBA
Mounting	Mounts into standard Decora-style wall plates
Colors Available	White: MET-6NE-WH (FG5793-01-WH) Black: MET-6NE-BL (FG5793-01-BL)
Recommended Accessories	<ul style="list-style-type: none"> •PS-POE-AF-TC, PoE Injector, 802.3AF Compliant (FG423-83)

POWER	
PoE	PoE (Power over Ethernet), 802.3af, class 0
Power Connector	(1) RJ-45 Ethernet Connector, 10/100

POWER SUPPLY	
External, Required	POE injector or switch, conforming to the 802.3af standard including AMX's PS-POE-AF-TC (FG423-83), not included

ETHERNET	
Ethernet Connection	(1) RJ-45 Ethernet Connector, 10/100

ENVIRONMENTAL	
Temperature (Operating)	32° to 104° F (0° to 40° C)
Humidity (Relative)	5% to 85%, non-condensing
Note	Intended for indoor use only

FRONT PANEL COMPONENTS	
Front Panel Components	<ul style="list-style-type: none"> •Pushbuttons available in a variety of field replaceable pre-printed buttons •Blue LEDs indicate activity •Navigation wheel •Light-level feedback •Sensor, 38 kHz only; supports standard AMX IR

REAR PANEL COMPONENTS	
Rear Panel Components	<ul style="list-style-type: none"> •(1) RJ-45 Ethernet Connector, 10/100 •(2) 8-pin, 0.100" (2.54 mm) IDC-type male header

About AMX

AMX hardware and software solutions simplify the implementation, maintenance, and use of technology to create effective environments. With the increasing number of technologies and operating platforms at work and home, AMX solves the complexity of managing this technology with reliable, consistent and scalable systems. Our award-winning products span control and automation, system-wide switching and audio/video signal distribution, digital signage and technology management. They are implemented worldwide in conference rooms, homes, classrooms, network operation / command centers, hotels, entertainment venues, broadcast facilities, and more. ©2014 AMX. All rights reserved.

Specifications subject to change. Revised 2025-03-12.

AMX.com | 800.222.0193 | 469.624.8000 | +1.469.624.7400 | fax 469.624.7153